



lount Height: 20ft

Grid Width: 60ft Total LLF: 1

# LavaLux LED

PRODUCT SPECIFICATION SHEET

LED STREET/AREA LIGHT

SL-45

#### **DESCRIPTION:**

THE SL-45 IS AN LED STREET LIGHT DESIGNED TO REPLACE A 75 WATT METAL HALIDE OR HIGH PRESSURE SODIUM LIGHT. THE SL-45 GIVES YOU MORE THAN 50% ENERGY SAVINGS OVER AN EXISTING CONVENTIONAL LIGHT SOURCE. THE SL-45 IS USED IN ROADWAY AND PARKING LOT ILLUMINATION.

#### **FEATURES:**

- **♣** OVER 50% ENERGY SAVINGS
- ♣ LONG LIFE PRESENTS MAINTENANCE SAVINGS
- **♣** 70% LIGHT OUTPUT AT 50K HRS
- ♣ LEDS OF THE HIGHEST EFFICIENCY
- # EASY TO INSTALL
- CUSTOMIZABLE TO YOUR LIGHTING REQUIREMENTS
- # MADE IN THE USA

# SPECIFICATIONS:

LIGHT OUTPUT 2700 LUMENS

COLOR 6500k (COOL WHITE)

INPUT VOLTAGE 100-240 VAC INPUT FREQUENCY 50-60 HZ INPUT POWER 41 WATTS POWER SUPPLY SAFETY UL 1310

OPERATING TEMPERATURE -40 TO 120 DEG F.

SL-45 WITH SOLAR OPTION

## **OPTIONS:**

- PROGRAMMABLE PHOTOCELL (ADDED ENERGY SAVINGS)
- SOLAR POWERED

## CONTACT:

LAVALUX LED 1693 MERCHANT STREET AMBRIDGE, PA 15003 TEL: 724-624-1191 FAX:724-266-1109

EMAIL: ASHOK.GIDWANI@LAVALUXLED.COM